Already over 15,000 users around the world

Second generation of the popular Pilkemaster firewood processors

The **Pilkemaster EVO** is a progressive firewood processor that adapts to your specific needs. **EVO** is the fastest firewood processor on the market, as you can move logs on the feeding table and cut them swiftly with the autolubricated chainsaw with a single motion. Thanks to the ingenious structure of the saw,

the chain speed is high and the cutting motion is fast and requires little force. The hydraulic log lifter and feed roller make operating the machine fast and effortless. The open structure underneath the splitting unit allows for sawdust and other by-products to pass through and avoids any build-up inside the machine.

The 4-metre long laterally turning conveyor enables you to discharge firewood into three large sacks, for example, without moving the machine. The folding conveyor and beam make transportation a breeze. Equipped with a separate transport chassis, the Pilkemaster can be easily transported by car.

Comprehensive accessories as standard

- Patented V-shaped feeding table
- Auto-lubricated chainsaw
- Height adjustment of the machine
- 4-way splitting blade
- Laterally turning conveyor, 4 m / 13.12 ft

Further accessory options

- Mobil road traffic model with brakes
- Mobil road traffic model without brakes
- Oil cooler
- Convenient log deck
- · Hydraulic log lifter
- Hydraulic feed roller (As standard in the EVO 36 HC)
- Optional separate postsplitting
- 6- or 8-way splitting

	EVO 30	EVO 36	EVO 36 HC LITE	EVO 36 HC
Firewood length	max. 60 cm / 23.6"	max. 60 cm / 23.6"	max. 60 cm / 23.6"	max. 60 cm / 23.6"
Maximum log diameter	30 cm / 11.8"	36 cm / 11.8"	36 cm / 11.8"	36 cm / 11.8"
Splitting force	3.5 tn standard. 5.6 tn accessory	2–8 tn (automatic adjustment)	2–8 tn (automatic adjustment)	2–8 tn (automatic adjustment)
Cutting and splitting speed (strong / normal / fast)	1.5 / 1.0 s (3.5 tn.) 2.4 / 1.6 s (5.6 tn.)	3.0 / 1.5 / 1.0 s	3.0 / 1.5 / 1.0 s	3.0 / 1.5 / 1.0 s
Drive	PTO, Gasoline, Electric	PTO, Gasoline, Electric	PTO, Gasoline, Electric	PTO, Gasoline, Electric
Splitting blade	hardened steel 0/2, 2/4 or 2/6	hardened steel 0/2, 2/4, 2/6 or 2/8	hardened steel 0/2, 2/4, 2/6 tai 2/8	hardened steel 0/2, 2/4, 2/6 or 2/8
Chainsaw blade	15" (18"/72)	15" (18"/72)	15" (18"/72)	15" (18"/72)
Laterally turning conveyor	0.24 m x 4 m / 9.45" x 13.12 ft	0.24 m x 4 m / 9.45" x 13.12 ft	0.24 m x 4 m / 9.45" x 13.12 ft	0.24 m x 4 m / 9.45" x 13.12 ft
Weight	645-730 kg	665-740 kg	685-760 kg	685-760 kg

*For full technical details, visit pilkemaster.com